ift-Nachweis

Classification Report

19-002257-PR04 (NW-H05-05-en-01)

Owner VITROFORM Sp. z o.o.

Cichawa 152 32-420 Gdów Poland

Product Laminated safety glass (LSG)

Designation Shipping name: VSG 66.2 EVA

Overall dimensions (W x H): (876 x 1938) mm, material: Float glass ExtraClear[®], Glass configuration: float glass 6 mm / EVA 0.76

mm / float glass 6 mm, Thickness: 12.76 mm, measured thickness:

12.27 mm

Special features -/-

Result

Number

Classification Pendulum Test according EN 12600



Class: 1 - (B) - 1

ift Rosenheim 23.01.2020

Frank Zirbel, Dipl.-Ing. (FH) Head of Testing Department Security/Safety Testing Khalid El Harda, Dipl.-Ing. (FH) Operating Testing Officer Security/Safety Testing



Basis *)

EN 12600:2002-11

*) and corresponding national versions (e.g. DIN EN)

Test report: 19-002257-PR04 PB-H05-05-en-01

Representation



Instructions for use

The results obtained can be used as evidence in accordance with the above basis.

Validity

There is no time limit.

When using this document the upto-dateness of above basis and the conformity of the product have to be observed.

The data and detailed results given relate solely to the test-ed/described specimen.

This test does not allow any statement to be made on further characteristics of the present structure regarding performance and quality, in particular the effects of weathering and ageing. The classification will be valid as long as the product remains unchanged and the above bases have not changed.

Notes on publication

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies.

Identity-Check



www.ift-rosenheim.de/ift-geprueft ID: 123-5C5FA



